

Description

- Heavy Duty Laminate
- Blockout to eliminate light permeating
- National FR standard in tent industry - California Sate (CSFM)

Details

CATEGORY	ENGLISH	METRIC	TEST METHOD
TOTAL WEIGHT	16 oz. per yard ²	542 g/m ²	FS 5040 / ASTM D3776
WIDTH	up to 61"	up to 155 cm	
CONSTRUCTION	9 x 9/1" by 1000	4 x 4/cm by 1100	
GRAB TENSILE	267 x 230 lbs./1"	1188 x 1023 N/2.5 cm	FS 5102 / ASTM D5035
TONGUE TEAR	62 x 62 lbs./1"	276 x 276 N/2.5	FS 5134 / ASTM D2261
ADHESION	32 lbs./2"	142 N/5 cm	FS 5970 / ASTM D751
TREATMENTS	Anti-Mildew, UV Pigments		
FINISH	Gloss		
FIRE RETARDANT	Pass		California State (CSFM)
PUT UP	75 yards	69 m	

The following information in regards to the chemical and physical properties of this product is based upon reliable testing methods. While reliable, these statistics are intended only as an informational source for your benefit. These statistics are however, provided only as a convenience and do not constitute a warranty and/or guarantee. The Purchaser is still required to determine if the product represented meets the individual needs of the Purchaser.