

Description

Providing protection from harmful UV radiation, yet still allows viewing through material. These flame retardant vinyl welding curtains are also oil water, & mildew resistant. Recommended for vertical use only, these curtains offer grinding, light sparking. dust / splash / spray confinement for welding enclosures. Special Features include: tinted screen, CSFM fire rating, UV stabilized - 0°F cold crack, lightly dusted.


Details

ROLL SIZE			
THICKNESS	14 MIL ± 5%		
WIDTH	66" + 1/4" - 0"		
LENGTH	101 YARDS		
NET WEIGHT	150 lbs. * ± 3%		
YARD YIELD	0.673		
MATERIAL DESCRIPTION			
FINISH	Double Polished		
HAND	Soft - 2S		
COLOR	Aztec Red, Yellow, Blue, Dark Green Shade 8, Charcoal		
PHYSICAL PROPERTIES			
TENSILE STRENGTH	MD	2700	ASTM-D-882
(PSI)	CD	2550	
ELONGATION	MD	240	ASTM-D-882
(%)	CD	260	
TEAR STRENGTH	MD	330	ASTM-D-1004
(LBS./IN)	CD	330	
HEAT SHRINKAGE	MD	-5	ASTM-D-1004
(%)	CD	+2	
Shipped in a box, rolled in craft paper on 3" I.D. Cores.			

*Shipped weight: Add 12 lbs. to net weight

Our technical sales representatives will assist you with your project requirements.
Give us a call today at **847-439-4565** for a quote!





Our technical sales representatives will assist you with your project requirements.
Give us a call today at **847-439-4565** for a quote!

