

Description

- Extremely Strong and Durable
- Anti-Mildew Treatments & U.V. Pigments
- Fire Retardant
- C.P.S.I.A. Certified (6P) and has No Detection of DnHP (7P)
- Less than 100 ppm Lead
- Leather Grain Finish

Details

CATEGORY	TEST RESULT	TEST METHOD
TOTAL WEIGHT	16 oz. per yard ²	FS 5040 / ASTM D3776
WIDTH	Up to 61"	
CONSTRUCTION	20 x 20/1" by 1000 x 1000	
GRAB TENSILE	450 x 505 lbs./1"	FS 5100 / ASTM D5034
TONGUE TEAR	75 x 75 lbs.	FS 5134 / ASTM D2261
ADHESION	25 lbs./2"	FS 5970 / ASTM D751
COLD CRACK	-30° F	FS 5874 / ASTM D 2136
F.R. TREATMENTS	Pass	ASTM E-84 / NFPA - 701 / CSFM
TREATMENTS	Anti-mildew, UV	
FINISH	Cow Leather	
PUT UP	75 yards	

The following information in regards to the chemical and physical properties of this product is based upon reliable testing methods. While reliable, these statistics are intended only as an informational source for your benefit. These statistics are however, provided only as a convenience and do not constitute a warranty and/or guarantee. The Purchaser is still required to determine if the product represented meets the individual needs of the Purchaser.