

Description

- A Good Fit for Tough Environments
- High Tensile and Tear-Strength
- Anti-Mildew / Anti-Microbial Treatments & U.V. Pigments
- Fire Retardant
- Latex and Rubber Free
- Matte Finish

Details

CATEGORY	TEST RESULT	TEST METHOD
TOTAL WEIGHT	18 oz. per yard ²	FS 5040 / ASTM D3776
WIDTH	61"	
CONSTRUCTION	18 x 17/1" by 1000 x 1000	
GRAB TENSILE	375 x 375 lbs./1"	FS 5100 / ASTM D5034
TONGUE TEAR	100 x 100 lbs.	FS 5134 / ASTM D2261
ADHESION	26 lbs./2"	FS 5970 / ASTM D751
COLD CRACK	-30° F	FS 5874 / ASTM D 2136
F.R. TREATMENTS	Self-extinguishing / Passes FR	CSFM / NFPA - 701
TREATMENTS	UV, Anti-microbial, Anti-bacterial, Anti-mildew, & Anti-mold	
FINISH	Matte	
PUT UP	75 yards	

The following information in regards to the chemical and physical properties of this product is based upon reliable testing methods. While reliable, these statistics are intended only as an informational source for your benefit. These statistics are however, provided only as a convenience and do not constitute a warranty and/or guarantee. The Purchaser is still required to determine if the product represented meets the individual needs of the Purchaser.