

Description

Advantage MVP 22 is a sturdy 22 oz coated formula well equipped to handle adverse weather conditions and withstand great physical stress. Advantage MVP 22 is well suited for Truck Tarp and Oil Boom applications. Its well designed construction allows it to remain flexible even in cold temperatures, making it ideal for the long haul or use on water for oil spill containment.

Details

	ENGLISH	METRIC	TESTING METHOD
WEIGHT	22 oz/yd²	745 g/m²	FS 5040 / ASTM D3776
WIDTHS	up to 126"	up to 320 cm	
CONSTRUCTION	18 x 16'1 by 1300 x 1500	7x6/cm by 1430 x 1650	
GRAB TENSILE	459 x 418 lbs./1"	2042x1859 M/2.5cm	FS 5100 / ASTM D5304
TONGUE TEAR	140 x 150 lbs./2"	623 x 667 N/2.5 cm	FS 5970 / ASTM D2261
ADHESION	22 lbs. /2"	98 N.5cm	FS 5874 / ASTM D751
FINISH	Matte		
COLD CRACK	-30℃	-34°C	FS 5874 / ASTM D2136
TREATMENTS	Anti-Mildew, UV		
FIRE RETARDANT	Self Extinguishing		Pass

Product Uses & Applications







Roll Tarps



Truck Tarps

