

## Description

Anti-Static NFPA701, UV, CC

## **Details**

ROLL SIZE			
THICKNESS	20 MIL ± -5%		
WIDTH	54" = ¼" - 0"		
LENGTH	58 yards		
NET WEIGHT	100 lbs.* ± 3%		
YARD YIELD	.58		
MATERIAL DESCRIPTION			
FINISH	Super Double Polished		
HAND	Soft - 3S		
COLOR	Clear		
SPECIFIC FEATURES			
Anti-Static			
Non-Phthalate			
Compliant NFPA701			
UV Stabilized			
-10 Cold Crack Rating			
PHYSICAL PROPERTIES			
TENSILE STRENGTH (PSI)	MD CD	2700 2500	ASTM-D-882
ELONGATION (%)	MD CD	240 260	ASTM-D-882
TEAR STRENGTH (lbs. / in)	MD CD	330 330	ASTM-D-1004
HEAT SHRINKAGE (%)	MD CD	-5 +2	ASTM-D-1004

Shipped in a box, rolled in craft paper on 3" I.D. Cores

Note: The information contained herein is believed to be reliable but no representatives, guarantees or warranties of any kind are made as to its accuracy or sustainability for particular applications



Our technical sales representatives will assist you with your project requirements. Give us a call today at **847-439-4565** for a quote!